



JV120005

**Bronze
Straight Pattern
Landing / Dry Riser Valve
Gate Valve**

**BS336 Instantaneous Outlet
Flanged or Threaded Inlet**

**PN16
BS 10 D/E
BSPT Female or Male
(Specify when enquiring)**



This fire hydrant gate valve with screwed bonnet is usually installed in building dry riser system.

It is manufactured to a high standard with high quality casting and precision machined metal to metal seats.

Available with PN16, BS Table D and BSPT female/male connections with a BS336 Instantaneous outlet.

Approvals, Features & Benefits

- BS5041 part 2
- Compact design
- High flow characteristics
- Suited for dry riser systems
- British BS336 instantaneous outlet
- Supplied with cap & chain

Pressure & Temperature

Maximum pressure:-
16 Bar

Temperature range:-
0°C to 38°C

DN65	Flanged PN16	Flanged BS Table D/E	Threaded 2½" BSPT Female	Threaded 2½" BSPT Male
A	150	150	150	180
B	185	185	185	185
C	140	140	140	140
D	185	165	-	-
E (PCD)	145	127	-	-
Weight Kg	7.5	7.0	6.0	6.0

MATERIALS

Body	Bronze
Bonnet	Brass
Stem	Brass
Handwheel	Cast Iron



Optional International Outlets

Available in the following:-

Storz • Gost • NST
NOR • SMS • Form 63
Guillemin • Nakajima • ROTA

